



Inter American Resins

ECO-PATCH HEAVY DUTY ECOLOGIC REPAIR SYSTEM

TECHNICAL DATA

ECO-PATCH

DESCRIPTION:

Eco-Patch is a fast-setting, polyurethane cement mortar designed to repair damaged concrete surfaces. It is friendly to the environment due to the nature of its components. Ideal for quick repairs to production and traffic areas.

Eco-Patch is formulated to achieve an easy to install, long lasting repairs under a wide variety of operating conditions. It is (virtually) odorless, allowing repairs to be performed without affecting production. Eco-Patch Kits covers approx. 15 sf. @ 1/4".

FEATURES AND BENEFITS:

- Low Odor
- Strong Adhesion
- Easy to Apply
- Fast Installation
- Sanitary
- Long Lasting
- Impervious
- Excellent Wear Resistant
- Abrasion Resistant
- Hygienic
- Impact Resistant
- Moisture Tolerant
- Withstand Heavy Traffic
- "Green" by LEED Standards
- Thermal Shock Resistant
- Full Cure in 4 hours

PACKAGING:

Eco-Patch is available in five gallons standard kit.

RECOMMENDED FOR:

- Agricultural
- Aircraft Hangars
- Airports
- Auto Dealers
- Bakeries
- Beverage Plants
- Breweries
- Chemical Processing Plants
- Coolers
- Commercial Kitchens
- Containment Area
- Correctional Facilities
- Corridors
- Docks/Ramps
- Dairies
- Distilleries
- Food Distributors
- Garages
- Hospitals
- Laboratories
- Laundries
- Machine Shops
- Manufacturing Plants
- Meat, Fish, Poultry Processing Plants
- Mechanical Equipment Rooms
- Medical Devices Plants
- Munitions Facilities
- Parking Garages
- Pharmaceuticals Plants
- Pulp and Paper Processing Facilities
- Restaurants
- Schools
- Shopping Malls
- Supermarkets
- Utilities
- Warehouses
- Waste Water Treatment Facilities

Inter American Resins

P.O. Box 4156, Vega Baja, P. R. 00693-4156 • 1-855-777-7998 • www.iaresins.com

TECHNICAL DATA

Eco Patch

Test	Result	Method
Viscosity	Mortar Consistency	n/a
Cure Time	4 hours @ 80°F	n/a
Compressive Strength	8,200 psi	ASTM C 109

SAFETY:

Eco-Patch contains Amines curing agents. Protective clothing and gloves are recommended to prevent skin contact to these materials. In case of ingestion or eye contact, contact a physician immediately. MSDS area available for this product upon request.

WARRANTY:

For product warranty see Inter American Resins, Corp. "Standard Limited Warranty". If one is not included with this literature, please call 1-855-777-7998 for further information or www.iaresins.com.

MAINTENANCE:

Water or detergents can be used to remove residue from equipment if it is clean before the material has started to set up; otherwise, stronger solvent such as methylene chloride will be necessary. Refer to MSD sheet for clean-up materials.